

**Declaration of Performance
DoP MTP-en**



1. Product type MTP anchor

2. Identification

Code	L – Length [mm]	Metric [mm]	Ø Outer diameter [mm]	Fixture thickness [mm]
AP08LLL	3 last digits of product code	M8	8	L-66
AP10LLL		M10	10	L-80
AP12LLL		M12	12	L-96
AP16LLL		M16	16	L-117
AP20LLL		M20	20	L-138
AP24LLL		M24	24	L-170

3. Intended use

Generic type: Torque controlled expansion anchor throughbolt type

Base material: Concrete C20/25 to C50/60 according to EN 206-1

Material: Made of steel, zinc plated ISO 4042 A2

Durability: Internal dry conditions

Loading: Static, quasi static loads

Fire resistance: F120

Seismic category C1 and C2

Assumed working
life: 50 years

4. Manufacturer

Index Fixing Systems. Técnicas Expansivas S.L.
Segador, 13
26006 Logroño, La Rioja, SPAIN

5. Authorized
representative

No applicable

6. System of
assessment of
performance:

1

7. Harmonized
standard:

No applicable

8. European technical assessment: Technical assessment body: IETcc; Instituto Eduardo Torroja de ciencias de la construcción. Notified body 1219.
- Issued: ETA 12/0397
- On the basis of: EAD 330232-00-0601
- Performed: Determination of product type, initial inspection of the manufacturing plant and continuous surveillance of FPC
- Under system: 1
- Issued: Certificate CE 1219-CPR-0053
9. Declared performances: Mechanical anchor for structural applications in concrete

Essential characteristics			Performance					
			M8	M10	M12	M16	M20	M24
Installation parameters								
d _o	Nominal diameter of drill bit:	[mm]	8	10	12	16	20	24
h _{ef}	Effective embedment depth:	[mm]	48	60	70	85	100	125
d _f	Fixture clearance hole diameter:	[mm]	9	12	14	18	22	26
T _{inst}	Nominal installation torque:	[Nm]	20	40	60	100	200	250
h ₁	Depth of drilled hole:	[mm]	60	75	85	105	125	155
h _{nom}	Minimum installation depth:	[mm]	55	68	80	97	114	143
h _{min}	Minimum thickness of concrete member:	[mm]	100	120	140	170	200	250
s _{min}	Minimum spacing:	[mm]	50	60	70	85	100	125
c _{min}	Minimum edge distance:	[mm]	50	60	70	85	100	125
Tension load: steel failure								
N _{Rk,s}	Tension steel characteristic resistance:	[kN]	18.1	31.4	40.4	72.7	116.6	179.2
γ _{Ms}	Partial safety factor:	[-]	1.5	1.5	1.5	1.5	1.5	1.5
Tension load: pull-out failure in concrete								
N _{Rk,p,ucr}	Tension characteristic resistance in C20/25 uncracked concrete:	[kN]	9	16	20	35	50	50
N _{Rk,p,cr}	Tension characteristic resistance in C20/25 cracked concrete:	[kN]	5	9	12	25	30	30
γ _{ins} ¹⁾ γ ₂ ²⁾	Partial safety factor:	[-]	1.2	1.0	1.0	1.0	1.0	1.2
ψ _c	C30/37	[-]	1.22	1.16	1.22	1.22	1.16	1.22
ψ _c	C40/45	[-]	1.41	1.31	1.41	1.41	1.31	1.41
ψ _c	C50/60	[-]	1.55	1.41	1.55	1.55	1.41	1.55
Tension load: concrete cone or splitting failure in concrete								
h _{ef}	Effective embedment depth:	[mm]	48	60	70	85	100	125
k ₁ =k _{ucr,N} ¹⁾	Factor for uncracked concrete:	[-]	11.0	11.0	11.0	11.0	11.0	11.0
k ₁ =k _{cr,N} ¹⁾	Factor for cracked concrete:	[-]	7.7	7.7	7.7	7.7	7.7	7.7
k ₁ ²⁾	Factor for uncracked concrete:	[-]	10.1	10.1	10.1	10.1	10.1	10.1
k ₁ ²⁾	Factor for cracked concrete:	[-]	7.2	7.2	7.2	7.2	7.2	7.2
γ _{ins} ¹⁾ γ ₂ ²⁾	Partial safety factor:	[-]	1.2	1.0	1.0	1.0	1.0	1.2
s _{cr,N}	Critical spacing:	[mm]	144	180	210	255	300	375
s _{cr,sp}	Critical spacing (splitting):	[mm]	288	300	350	425	500	560
c _{cr,N}	Critical edge distance:	[mm]	72	90	105	128	150	188
c _{cr,sp}	Critical edge distance (splitting):	[mm]	144	150	175	213	250	280
Displacements under tension loads								
N	Service tension load:	[kN]	2.5	4.3	6.3	10.4	13.9	18.0
δ _{N0}	Short term displacement under tension loads:	[mm]	1.1	0.7	1.0	0.4	1.6	0.4
δ _{N∞}	Long term displacement under tension loads:	[mm]	1.9	1.9	1.9	1.9	1.9	2.0
Shear load: steel failure without lever arm								
V _{Rk,s}	Characteristic resistance:	[kN]	11.0	17.4	25.3	47.1	73.1	84.7
k ₂ ¹⁾	k ₂ factor:	[-]	1.0	1.0	1.0	1.0	1.0	1.0
k ₇ ²⁾	k ₇ factor:	[-]	1.0	1.0	1.0	1.0	1.0	1.0
γ _{Ms}	Partial safety factor:	[-]	1.25	1.25	1.25	1.25	1.25	1.25
Shear load: steel failure with lever arm								
M ⁰ _{Rk,s}	Characteristic bending moment:	[Nm]	22.5	44.8	78.6	199.8	389.4	673.5
γ _{Ms}	Partial safety factor:	[-]	1.25	1.25	1.25	1.25	1.25	1.25

Essential characteristics		Performance					
		M8	M10	M12	M16	M20	M24
Shear load: concrete pryout failure							
$k_3^{1)2)}$ $k^{3)}$ k factor:	[-]	1	2	2	2	2	2
$\gamma_{ins}^{1)2)}$ $\gamma_2^{3)}$ Installation safety factor:	[-]	1.0	1.0	1.0	1.0	1.0	1.0
Shear load: concrete edge failure							
l_f Effective length of anchor under shear loads:	[mm]	48	60	70	85	100	125
d_{nom} Outside anchor diameter:	[mm]	8	10	12	16	20	24
$\gamma_{ins}^{1)2)}$ $\gamma_2^{3)}$ Installation safety factor:	[-]	1.5	1.5	1.5	1.5	1.5	1.5
Displacements under shear loads							
V Service shear load:	[kN]	4.9	6.8	8.5	15.1	24.6	33.6
δ_{V0} Short term displacement:	[mm]	1.0	1.5	1.8	1.9	3.1	1.4
$\delta_{V\infty}$ Long term displacement:	[mm]	1.5	2.3	2.7	2.9	4.7	2.1

¹⁾ Parameter relevant only for design according to CEN/TS 1992-4:2009

²⁾ Parameter relevant only for design according to prEN 1992-4

³⁾ Parameter relevant only for design according to ETAG 001, Annex C

Information for seismic design seismic category C1		Performance					
		M8	M10	M12	M16	M20	M24
Steel failure for tension and shear failure							
$N_{Rk,s,seis}$ Characteristic tension steel failure:	[kN]	--	31.4	40.4	72.7	--	--
$\gamma_{Ms,N}$ Partial safety factor:	[-]	--	1.5	1.5	1.5	--	--
$V_{Rk,p,seis}$ Characteristic shear steel failure:	[kN]	--	12.2	17.8	33.0	--	--
$\gamma_{Ms,V}$ Partial safety factor:	[-]	--	1.25	1.25	1.25	--	--
Pull out failure							
$N_{Rk,p,seis}$ Characteristic pull out failure:	[kN]	--	5.3	8.4	17.5	--	--
Concrete cone failure							
h_{ef} Effective embedment depth:	[mm]	--	60	70	85	--	--
$s_{cr,N}$ Spacing:	[mm]	--	180	210	255	--	--
$c_{cr,N}$ Edge distance:	[mm]	--	90	105	128	--	--
$\gamma_{ins}^{1)}$ $\gamma_2^{2)}$ Installation safety factor:	[-]	--	1.0	1.0	1.0	--	--
Concrete pryout failure							
$k_3^{1)}$ $k^{2)}$ k factor:	[-]	--	2	2	2	--	--
Concrete edge failure							
l_f Effective length of anchor:	[mm]	--	60	70	85	--	--
d_{nom} Outside anchor diameter:	[mm]	--	10	12	16	--	--

Information for seismic design seismic category C2		Performance					
		M8	M10	M12	M16	M20	M24
Steel failure for tension and shear failure							
$N_{Rk,s,seis}$ Characteristic tension steel failure:	[kN]	--	--	40.4	72.7	--	--
$\gamma_{Ms,N}$ Partial safety factor:	[-]	--	--	1.5	1.5	--	--
$V_{Rk,p,seis}$ Characteristic shear steel failure:	[kN]	--	--	17.8	33.0	--	--
$\gamma_{Ms,V}$ Partial safety factor:	[-]	--	--	1.25	1.25	--	--
Pull out failure							
$N_{Rk,p,seis}$ Characteristic pull out failure:	[kN]	--	--	5.2	8.9	--	--
Concrete cone failure							
h_{ef} Effective embedment depth:	[mm]	--	--	70	85	--	--
$s_{cr,N}$ Spacing:	[mm]	--	--	210	255	--	--
$c_{cr,N}$ Edge distance:	[mm]	--	--	105	128	--	--
$\gamma_{ins}^{1)}$ $\gamma_2^{2)}$ Installation safety factor:	[-]	--	--	1.0	1.0	--	--
Concrete pryout failure							
$k_3^{1)}$ $k^{2)}$ k factor:	[-]	--	--	2	2	--	--
Concrete edge failure							
l_f Effective length of anchor:	[mm]	--	--	70	85	--	--
d_{nom} Outside anchor diameter:	[mm]	--	--	12	16	--	--

Information for seismic design seismic category C2			Performance					
			M8	M10	M12	M16	M20	M24
Concrete cone failure								
$\delta_{N,seis} (DLS)$	Displacement Damage Limitation State ^{3) 4)} :	[mm]	--	--	2.34	3.99	--	--
$\delta_{V,seis} (DLS)$	Displacement Damage Limitation State ^{3) 4)} :	[mm]	--	--	5.53	5.96	--	--
$\delta_{N,seis} (ULS)$	Displacement Ultimate Limit State ³⁾ :	[mm]	--	--	9.54	10.17	--	--
$\delta_{V,seis} (ULS)$	Displacement Ultimate Limit State ³⁾ :	[mm]	--	--	9.08	10.66	--	--

¹⁾ Parameter relevant only for design according to CEN/TS 1992-4:2009, prEN 1992-4

²⁾ Parameter relevant only for design according to ETAG 001, Annex C

³⁾ The listed displacements represent mean values

⁴⁾ A small displacement may be required in the design in the case of displacements sensitive fastening of "rigid" supports. The characteristics resistance associated with such small displacements may be determined by linear interpolation or proportional reduction.

Characteristic values for resistance to fire			Performance					
			M8	M10	M12	M16	M20	M24
Steel failure								
$N_{Rk,s,fi,30}$	Characteristic tension resistance, R30:	[kN]	0,4	0,9	1,7	3,1	4,9	7,1
$N_{Rk,s,fi,60}$	Characteristic tension resistance, R60:	[kN]	0,3	0,8	1,3	2,4	3,7	5,3
$N_{Rk,s,fi,90}$	Characteristic tension resistance, R90:	[kN]	0,3	0,6	1,1	2,0	3,2	4,6
$N_{Rk,s,fi,120}$	Characteristic tension resistance, R120:	[kN]	0,2	0,5	0,8	1,6	2,5	3,5
$V_{Rk,s,fi,30}$	Characteristic shear resistance, R30:	[kN]	0,4	0,9	1,7	3,1	4,9	7,1
$V_{Rk,s,fi,60}$	Characteristic shear resistance, R60:	[kN]	0,3	0,8	1,3	2,4	3,7	5,3
$V_{Rk,s,fi,90}$	Characteristic shear resistance, R90:	[kN]	0,3	0,6	1,1	2,0	3,2	4,5
$V_{Rk,s,fi,120}$	Characteristic shear resistance, R120:	[kN]	0,2	0,5	0,8	1,6	2,5	3,5
$M^0_{Rk,s,fi,30}$	Characteristic bending resistance, R30:	[kN]	0,4	1,1	2,6	6,7	13,0	22,5
$M^0_{Rk,s,fi,60}$	Characteristic bending resistance, R60:	[kN]	0,3	1,0	2,0	5,0	9,7	16,8
$M^0_{Rk,s,fi,90}$	Characteristic bending resistance, R90:	[kN]	0,3	0,7	1,7	4,3	8,4	14,6
$M^0_{Rk,s,fi,120}$	Characteristic bending resistance, R120:	[kN]	0,2	0,6	1,3	3,3	6,5	11,2
Pull out failure								
$N_{Rk,p,fi,30}$	Characteristic resistance, R30:	[kN]	1,3 ³⁾	2,3	3,0 ³⁾	6,3	7,5	7,5
$N_{Rk,p,fi,60}$	Characteristic resistance, R60:	[kN]	1,3 ³⁾	2,3	3,0 ³⁾	6,3	7,5	7,5
$N_{Rk,p,fi,90}$	Characteristic resistance, R90:	[kN]	1,3 ³⁾	2,3	3,0 ³⁾	6,3	7,5	7,5
$N_{Rk,p,fi,120}$	Characteristic resistance, R120:	[kN]	1,0 ³⁾	1,8	2,4 ³⁾	5,0	6,0	6,0
Concrete cone failure ⁴⁾								
$N_{Rk,p,fi,30}$	Characteristic resistance, R30:	[kN]	2.9	5,0	7,4	12,0	18,0	31,4
$N_{Rk,p,fi,60}$	Characteristic resistance, R60:	[kN]	2.9	5,0	7,4	12,0	18,0	31,4
$N_{Rk,p,fi,90}$	Characteristic resistance, R90:	[kN]	2.9	5,0	7,4	12,0	18,0	31,4
$N_{Rk,p,fi,120}$	Characteristic resistance, R120:	[kN]	2,3	4,0	5,9	9,6	14,4	25,2
$s_{cr,N,fi}$	Critical spacing, from R30 to R120:	[mm]	4 x h_{ef}	4 x h_{ef}	4 x h_{ef}	4 x h_{ef}	4 x h_{ef}	4 x h_{ef}
$s_{min,fi}$	Minimum spacing, from R30 to R120:	[mm]	50	60	70	85 ³⁾	100 ³⁾	125
$c_{cr,N,fi}$	Critical edge distance, from R30 to R120:	[mm]	2 x h_{ef}	2 x h_{ef}	2 x h_{ef}	2 x h_{ef}	2 x h_{ef}	2 x h_{ef}
$c_{min,fi}$	Minimum edge distance, from R30 to R120:	[mm]	$c_{min} = 2 \times h_{ef}$; si el ataque de fuego proviene de más de una cara, la distancia del anclaje al borde tiene que ser ≥ 300 mm y $\geq 2 \times h_{ef}$					
Concrete pry out failure								
$k_3=k_8^{1)}$ $k^{2)}$	K factor:	[-]	1	2	2	2	2	2

¹⁾ Parameter relevant only for design according to CEN/TS 1992-4:2009, prEN 1992-4

²⁾ Parameter relevant only for design according to ETAG 001, Annex C

³⁾ The listed displacements represent mean values

⁴⁾ A small displacement may be required in the design in the case of displacements sensitive fastening of "rigid" supports. The characteristics resistance associated with such small displacements may be determined by linear interpolation or proportional reduction.

- 10.** The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed on behalf of the manufacturer by:

A handwritten signature in black ink, appearing to read 'S. Reig', is written on the page.

Santiago Reig. Technical Manager
Logroño, 12.03.2018